


Feature rich programmable/non-programmable all-in-one thermostat

7-day • 5/2-day
Programmable • Non-Programmable

Product Highlights

- ✓ All in-one programmable/non-programmable
- ✓ 2-heat/1-cool heating & AC
- ✓ Dual powered
- ✓ Adjustable heating and cooling limits
- ✓ 3 year warranty
- ✓ Adjustable 2nd stage heat offset



Product Features

- Easy installation
- Program 7-day, 5/2-day, or non-programmable
- Easy-view back light
- Optional wall plate model #WP567
- User option: 2 or 4 periods per day
- Keypad lock for unauthorized use
- Temporary override and manual hold
- Dual powered (2AA) Alkaline Batteries (included)
- Temporary Compressor protection bypass
- 5/2 minute selectable time delay for equipment protection
- User temperature calibration
- Adjustable heating and cooling limits
- Display option: fahrenheit or celsius temperature
- Adjustable temperature differential/swing
- Conventional heat & heat pump

Installation

Compatible With


- For most 24V heating and A/C systems
- 2-heat/1-cool: gas, oil, or electric systems (Non-heat-pumps)
- 2-wire heat only hydronic systems (hot water baseboard & radiator)
- Millivolt systems (wall heaters/furnaces & gas fireplaces)

Not Compatible With

- Heat pump systems
- 3-wire hydronic zone valve systems
- Line voltage systems (120/240 VAC)

SPECIFICATIONS

MODEL# **P721**



Dimensions	5.375" (136mm) wide x 3.375" (86mm) tall x 1.25" (32mm) deep
Heat/Cool Terminals	RH, RC, W, Y, G, C, W2 (solid pins for 24v and Millivolt systems)
Electrical Ratings	1.5 Amps per terminal at 24 volts
Temperature Control Range	<ul style="list-style-type: none"> Temp control 45°F to 90°F (7°C to 32°C) Display range: 23°F to 99°F (-5°C to 37°C) Temperature Differential: adjustable from ±0.25°F to ±2.25°F <i>Accuracy ±1°F over a range of 45°F to 90°F.</i>
Environmental Limits	<ul style="list-style-type: none"> Moisture and Dust: meets IP20 Operating Humidity: 20% to 90% (non-condensating) Operating temperature: 14°F to 114°F (-10°C to 45°C) Storage temperature: -4°F to 140°F (-20°C to 60°C) Electrical Immunity: meets relevant EMI/EMC specifications
Compatible With	<ul style="list-style-type: none"> For most 24V heating and A/C systems 2-heat/1-cool: gas, oil, or electric systems (Non-heat-pumps) 2-wire heat only hydronic systems (hot water baseboard & radiator) Millivolt systems (wall heaters/furnaces & gas fireplaces)
Not Compatible With	<ul style="list-style-type: none"> Heat pump systems 3-wire hydronic zone valve systems Line voltage systems (120/240 VAC)
Packaging	<ul style="list-style-type: none"> Master Carton: 10 units UPC: 0 21079 14721 2

Project Name _____

Date _____

Contractor / Engineer _____

Location _____

